


## 1 Identification

- **Product identifier**
- **Trade name:** Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome
- **Article number:**  
256905, 263453 - 264436, 264757 / 264764, 265372, 272073 / 272080, 278310 - 278426, 282638 - 282683, 289941 / 289965, 295607, 298738, 314414 - 314469, 325489, 325496, 321337 - 321818, 351945 - 352317, 352232, 352249, 352256, 352263, 352300, 352317, 381126, 386312 - 386510, 425217, 429705, 431289
- **Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the mixture** *Lacquer*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MONTANA CANS  
Häusserstr. 36  
D-69115 Heidelberg  
Tel. +49-6221-36333-30  
Fax +49-6221-36333-33  
info@montana-cans.de  
www.montana-cans.com
- **Information department:** Department Product Safety
- **Emergency telephone number:**  
Tel.: +49 6266-75-310  
Fax +49 6266-75-362  
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)


## 2 Hazard(s) identification

- **Information concerning particular hazards for human and environment:**  
*The product has to be labeled due to the calculation procedure of international guidelines.  
Warning! Pressurized container.*


---

  - **Label elements**
  - **GHS label elements**  
*The product is classified and labeled according to the Globally Harmonized System (GHS).*
  - **Hazard pictograms**
- 

GHS02



GHS07



GHS08
- **Signal word** *Danger*
  - **Hazard-determining components of labeling:**  
*xylene, mixture of isomers  
titanium dioxide*
  - **Hazard statements**  
*Extremely flammable aerosol. Pressurized container: May burst if heated.  
Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of causing cancer.*
  - **Precautionary statements**  
*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe spray.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 1)

Dispose of contents / container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 4  
Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**



Health = 1  
Fire = 4  
Reactivity = 3

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7 Index number: 601-022-00-9 RTECS: ZE 2100000	xylene, mixture of isomers ☒ Xn R20/21; ☒ Xi R38 R10 ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	20-<25%
CAS: 67-64-1 Index number: 606-001-00-8 RTECS: AL 3150000	acetone ☒ Xi R36; 🔥 F R11 R66-67 ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	12.5-<20%
CAS: 74-98-6 Index number: 601-003-00-5 RTECS: TX 2275000	propane 🔥 F+ R12 ⚠ Flam. Gas 1, H220; Press. Gas, H280	12.5-<20%
CAS: 106-97-8 Index number: 601-004-00-0 RTECS: EJ 4200000	butane 🔥 F+ R12 ⚠ Flam. Gas 1, H220; Press. Gas, H280	5-<10%
CAS: 13463-67-7	titanium dioxide ⚠ Carc. 2, H351	5-<10%
CAS: 75-28-5 Index number: 601-004-00-0 RTECS: TZ 4300000	isobutane 🔥 F+ R12 ⚠ Flam. Gas 1, H220; Press. Gas, H280	2.5-<5.0%
CAS: 108-65-6 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate R10 ⚠ Flam. Liq. 3, H226	2.5-<5.0%
CAS: 64742-95-6 Index number: 649-356-00-4	Solvent naphtha (petroleum), light arom. ☒ Xn R65; ☒ Xi R37; ☒ N R51/53 R10-66-67 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304	<2.5%
CAS: 100-41-4 Index number: 601-023-00-4 RTECS: DA 0700000	ethylbenzene ☒ Xn R20-48/20-65; 🔥 F R11 ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	<2.5%

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 2)

· **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex I 67/548 EU), so the classification as carcinogen need not to apply.  
For the wording of the listed risk phrases refer to section 16.

## 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters -**

· **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow product to reach sewage system or any water course.

· **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 3)

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility: Not required.**

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **Storage class: 2B**

· **Specific end use(s) No further relevant information available.**

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems: No further data; see item 7.**

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**1330-20-7 xylene, mixture of isomers**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm

Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm

Long-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

**67-64-1 acetone**

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m<sup>3</sup>, (750) NIC-500 ppm

Long-term value: (1188) NIC-594 mg/m<sup>3</sup>, (500) NIC-250 ppm

BEI

**74-98-6 propane**

PEL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV refer to Appendix F

**106-97-8 butane**

REL Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm

**75-28-5 isobutane**

TLV Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL Long-term value: 50 ppm

· **Ingredients with biological limit values:**

**1330-20-7 xylene, mixture of isomers**

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 4)

**67-64-1 acetone**

<b>BEI</b>	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

Filter AX  
Not necessary if room is well-ventilated.

· **Protection of hands:**

Protective gloves

## Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Butyl rubber, BR· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min  
Butyl acetate: 60 min  
Ethyl acetate: 170 min  
Xylene: 42 min

· **Eye protection:** Safety glasses

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

<b>Form:</b>	Aerosol
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 365 °C (689 °F)

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 5)

· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
· <b>Explosion limits:</b>	
Lower:	1.1 Vol %
Upper:	13.0 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	8300 hPa (6226 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.98 g/cm <sup>3</sup> (8.178 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
VOC-USA	50.7 % 621.9 g/l / 5.19 lb/gl
· <b>Solids content:</b>	43.9 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 1330-20-7 xylene, mixture of isomers

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6350 mg/l (rat)

### 67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	3592 mg/kg (rat) (ECD-Prüfrichtlinie401)
------	------	--

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 6)

Dermal	LD50	>3160 mg/kg (rab) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
<ul style="list-style-type: none"> <li>· <b>Primary irritant effect:</b></li> <li>· <b>on the skin:</b> No irritant effect.</li> <li>· <b>on the eye:</b> No irritating effect.</li> <li>· <b>Sensitization:</b> No sensitizing effects known.</li> <li>· <b>Additional toxicological information:</b> The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Vapors have narcotic effect.</li> <li>· <b>Carcinogenic categories</b></li> </ul>		
· <b>IARC (International Agency for Research on Cancer)</b>		
1330-20-7	xylene, mixture of isomers	3
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
7631-86-9	silicon dioxide, chemically prepared	3
9002-88-4	Ethylen, Homopolymer	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

**1330-20-7 xylene, mixture of isomers**

EC50 (24h)	>175 mg/l (bacteria)
EC50 / 48h	3.82 mg/l (daphnia magna / Wasserfloh)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

EC50 / 48h	>100 mg/l (daphnia magna / Wasserfloh)
EC50/96h	19 mg/l (desmdesmus subspicatus / Grünalge) (OECD - Prüfrichtlinie 201)
LC50/96h	>100 mg/l (Regenbogenforelle) (67/548/EWG Annex 5 C.1.)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**




· **Other adverse effects** No further relevant information available.

(Contd. of page 7)

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>  | <p style="margin-left: 20px;">UN1950</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul> | <p style="margin-left: 20px;">Aerosols, flammable<br/>UN1950 Aerosols<br/>AEROSOLS<br/>AEROSOLS, flammable</p>   |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>  | <div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> |
| <ul style="list-style-type: none"> <li>· <b>ADR</b></li> </ul>   | <div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> |
| <ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>  | <div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> |
| <ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>  | <p style="margin-left: 20px;">Void</p>   |
| <ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>  | <p style="margin-left: 20px;">No</p>   |
| <ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Danger code (Kemler):</b></li> <li>· <b>EMS Number:</b></li> </ul>                | <p style="margin-left: 20px;">Warning: Gases<br/>-<br/>F-D,S-U</p>   |

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 8)

- |  |  |
|--|--|
| <b>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.                                |
| <b>· Transport/Additional information:</b>                                       |  |
| <b>· ADR</b>   |  |
| <b>· Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity |
| <b>· IMDG</b>  |  |
| <b>· Limited quantities (LQ)</b>   | 1L   |
| <b>· Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity |
| <b>· UN "Model Regulation":</b>  | UN1950, Aerosols, 2.1                          |

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture .
- Sara

**· Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

**· Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene, mixture of isomers
100-41-4	ethylbenzene

**· TSCA (Toxic Substances Control Act):**

1330-20-7	xylene, mixture of isomers
67-64-1	acetone
74-98-6	propane
106-97-8	butane
13463-67-7	titanium dioxide
75-28-5	isobutane
108-65-6	2-methoxy-1-methylethyl acetate
1345-05-7	Zinksulfid-Barium-Mischsalz
64742-95-6	Solvent naphtha (petroleum), light arom.
100-41-4	ethylbenzene
7631-86-9	silicon dioxide, chemically prepared
9002-88-4	Ethylen, Homopolymer
96-29-7	2-butanone oxime
147900-93-4	fatty acids
64742-48-9	Naphtha (petroleum), hydrotreated heavy

**· Proposition 65**

**· Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
14808-60-7	Quartz (SiO <sub>2</sub> )

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 9)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene, mixture of isomers	I
67-64-1	acetone	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene, mixture of isomers	A4
67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
100-41-4	ethylbenzene	A3
14808-60-7	Quartz (SiO <sub>2</sub> )	A2

· **MAK (German Maximum Workplace Concentration)**

13463-67-7	titanium dioxide	3A
100-41-4	ethylbenzene	3A
96-29-7	2-butanone oxime	2
14808-60-7	Quartz (SiO <sub>2</sub> )	1

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO <sub>2</sub> )

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

xylene, mixture of isomers  
titanium dioxide

· **Hazard statements**

Extremely flammable aerosol. Pressurized container: May burst if heated.  
Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of causing cancer.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe spray.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents / container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R36 Irritating to eyes.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

· **Contact:**

· **Date of preparation / last revision** 08/19/2015 / 16

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
- Carc. 2: Carcinogenicity, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(Contd. on page 12)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 08/19/2015

Reviewed on 08/19/2015

**Trade name: Montana Black Lackspray 150 / 400ml all Colors, silver-, gold- und copperchrome**

*STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2*  
*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*

(Contd. of page 11)

USA