

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Montana WHITE all colours
- **Article number:** 280030 - 280429, 344237 - 344336
- **1.2 Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the mixture** Lacquer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MONTANA CANS
Häusserstr. 36
D-69115 Heidelberg
Tel. +49-6221-36333-30
Fax +49-6221-36333-33
info@montana-cans.de
www.montana-cans.com
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**
Tel.: +49 6266-75-310
Fax +49 6266-75-362
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Acute Tox. 4	H312	Harmful in contact with skin.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R67: Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Has a narcotising effect.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 10

Revision: 06.02.2015

Trade name: **Montana WHITE all colours**

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

xylene, mixture of isomers

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Xi R36; F R11 R66-67 <hr style="border-top: 1px dashed black;"/> Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane F+ R12 Flam. Gas 1, H220; Press. Gas C, H280	12.5-<20%

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 10

Revision: 06.02.2015

Trade name: Montana WHITE all colours

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers ☒ Xn R20/21; ☒ Xi R38 R10 ☒ Flam. Liq. 3, H226; ☒ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas C, H280	10-<12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas C, H280	2.5-<5.0%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 ☒ Flam. Liq. 3, H226	<2.5%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ☒ Xn R65; ☒ Xi R37; ☒ N R51/53 R10-66-67 ☒ Flam. Liq. 3, H226; ☒ Asp. Tox. 1, H304; ☒ Aquatic Chronic 2, H411; ☒ STOT SE 3, H335-H336	≤0.5%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim.
Vaten met water afkoelen.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters -**

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 10

Revision: 06.02.2015

Trade name: **Montana WHITE all colours**

(Contd. of page 3)

- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**
Do not flush with water or aqueous cleansing agents
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 2B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
1330-20-7 xylene, mixture of isomers	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
106-97-8 butane	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1,3-diene)
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 10

Revision: 06.02.2015

Trade name: Montana WHITE all colours

(Contd. of page 4)

· Ingredients with biological limit values:**1330-20-7 xylene, mixture of isomers**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

-
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

· Respiratory protection:

- Not necessary if room is well-ventilated.
- Otherwise, filter class A / P2 or self contained.

· Protection of hands:

Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Butyl rubber, BR**· Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

- Acetone: 480 min
- Butyl acetate: 60 min
- Ethyl acetate: 170 min
- Xylene: 42 min

· Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:**

- | | |
|---------------------------|------------------------------------|
| Form: | Aerosol |
| Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |

· **pH-value:** Not determined.

· Change in condition

- | | |
|-------------------------------------|-----------------------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | Not applicable, as aerosol. |

· **Flash point:** Not applicable, as aerosol.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 10

Revision: 06.02.2015

Trade name: **Montana WHITE all colours**

(Contd. of page 5)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	365 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20 °C:	8300 hPa
· Density at 20 °C:	0.83 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC-(EU)	---
	511.5 g/l
· VOC-EU%	61.54 %
· Solids content:	18.1 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values relevant for classification:		
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
1330-20-7 xylene, mixture of isomers		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 10

Revision: 06.02.2015

Trade name: Montana WHITE all colours

(Contd. of page 6)

Inhalative	LC50/4 h	6350 mg/l (rat)
------------	----------	-----------------

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitisation:** No sensitising effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Vapours have narcotic effect.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

1330-20-7 xylene, mixture of isomers

EC50 (24h)	>175 mg/l (bacteria)
------------	----------------------

EC50 / 48h	3.82 mg/l (daphnia magna / Wasserfloh)
------------	--

EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata)
----------	--

LC50/96h	7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)
----------	--

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

15 01 04	metallic packaging
----------	--------------------

15 01 11*	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers
-----------	---

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN1950

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 10

Revision: 06.02.2015

Trade name: **Montana WHITE all colours**

(Contd. of page 7)

· **14.2 UN proper shipping name**
 · **ADR** UN1950 AEROSOLS
 · **IMDG** AEROSOLS
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**

· **Class** 2 5F Gases.
 · **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1
 · **Label** 2.1

· **14.4 Packing group**· **ADR, IMDG, IATA** Void· **14.5 Environmental hazards:**· **Marine pollutant:** No· **14.6 Special precautions for user**

Warning: Gases.

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **14.7 Transport in bulk according to Annex II of
 MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .**· **Waterhazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 9)

Trade name: Montana WHITE all colours

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 *Extremely flammable gas.*
- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H280 *Contains gas under pressure; may explode if heated.*
- H304 *May be fatal if swallowed and enters airways.*
- H312 *Harmful in contact with skin.*
- H315 *Causes skin irritation.*
- H319 *Causes serious eye irritation.*
- H332 *Harmful if inhaled.*
- H335 *May cause respiratory irritation.*
- H336 *May cause drowsiness or dizziness.*
- H411 *Toxic to aquatic life with long lasting effects.*
- R10 *Flammable.*
- R11 *Highly flammable.*
- R12 *Extremely flammable.*
- R20/21 *Harmful by inhalation and in contact with skin.*
- R36 *Irritating to eyes.*
- R37 *Irritating to respiratory system.*
- R38 *Irritating to skin.*
- R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- R65 *Harmful: may cause lung damage if swallowed*
- R66 *Repeated exposure may cause skin dryness or cracking.*
- R67 *Vapours may cause drowsiness and dizziness.*

· **Contact: Anwendungstechnik**

· **Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- ICAO: *International Civil Aviation Organisation*
- ADR: *Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: *International Maritime Code for Dangerous Goods*
- IATA: *International Air Transport Association*
- GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: *European Inventory of Existing Commercial Chemical Substances*
- ELINCS: *European List of Notified Chemical Substances*
- CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
- VOC: *Volatile Organic Compounds (USA, EU)*
- LC50: *Lethal concentration, 50 percent*
- LD50: *Lethal dose, 50 percent*
- Flam. Gas 1: *Flammable gases, Hazard Category 1*
- Flam. Aerosol 1: *Flammable aerosols, Hazard Category 1*
- Press. Gas C: *Gases under pressure: Compressed gas*
- Flam. Liq. 2: *Flammable liquids, Hazard Category 2*
- Flam. Liq. 3: *Flammable liquids, Hazard Category 3*
- Acute Tox. 4: *Acute toxicity, Hazard Category 4*
- Skin Irrit. 2: *Skin corrosion/irritation, Hazard Category 2*
- Eye Irrit. 2: *Serious eye damage/eye irritation, Hazard Category 2*
- STOT SE 3: *Specific target organ toxicity - Single exposure, Hazard Category 3*
- Asp. Tox. 1: *Aspiration hazard, Hazard Category 1*
- Aquatic Chronic 2: *Hazardous to the aquatic environment - Chronic Hazard, Category 2*