

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *MONTANA GOLD Spray Paint all colors, fluo and shock*
- **Article number:**
283604 - 285844, 285899, 285905, 285929, 364945, 419331, 419348, 419355, 419362, 419379, 419386, 419393, 419409, 419416, 419423, 419430, 419447, 419454, 419461, 419478
- **1.2 Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the mixture** *Lacquer*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MONTANA CANS
Häusserstr. 36
D-69115 Heidelberg
Tel. +49-6221-36333-30
Fax +49-6221-36333-33
info@montana-cans.de
www.montana-cans.com
- **Further information obtainable from:** *Department Product Safety*
- **1.4 Emergency telephone number:**
Tel.: +49 6266-75-310
Fax +49 6266-75-362
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurised container.

Has a narcotising effect.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

ethyl acetate

acetone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether F+ R12 Flam. Gas 1, H220; Press. Gas C, H280	12.5-<20%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	12.5-<20%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: **MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 2)

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ☒ Xi R36; ☒ F R11 R66-67 ☒ Flam. Liq. 2, H225; ☒ Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas C, H280	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas C, H280	5-<10%
CAS: 64742-94-5 EINECS: 265-198-5 Index number: 649-424-00-3 Reg.nr.: 01-2119510128-50	Solvent naphtha (petroleum), heavy arom. ☒ Xn R65 ☒ Asp. Tox. 1, H304	2.5-<5.0%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 ☒ Flam. Liq. 3, H226	2.5-<5.0%
CAS: 9004-70-0 Index number: 603-037-00-6	cellulose nitrate ☒ E R3 ☒ Expl. 1.1, H201	2.5-<5.0%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers ☒ Xn R20/21; ☒ Xi R38 R10 ☒ Flam. Liq. 3, H226; ☒ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-<5.0%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane ☒ F+ R12 ☒ Flam. Gas 1, H220; Press. Gas C, H280	<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol ☒ Xi R36; ☒ F R11 R67 ☒ Flam. Liq. 2, H225; ☒ Eye Irrit. 2, H319; STOT SE 3, H336	<2.5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons ☒ Xn R65; ☒ Xi R37; ☒ N R51/53 R10-66-67 ☒ Flam. Liq. 3, H226; ☒ Asp. Tox. 1, H304; ☒ Aquatic Chronic 2, H411; ☒ STOT SE 3, H335-H336	<1.0%

· **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 3)

- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, bluspoeder of waterstraal. Grottere brand met waterstraal of met schuim.
Vaten met water afkoelen.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters -**

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 2B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: **MONTANA GOLD Spray Paint all colors, fluo and shock**

(Contd. of page 4)

· 8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:****115-10-6 dimethyl ether**

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

1330-20-7 xylene, mixture of isomers

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

· Ingredients with biological limit values:**1330-20-7 xylene, mixture of isomers**

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.
Otherwise, filter class A / P2 or self contained.

· Protection of hands:

Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Butyl rubber, BR

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

· **Eye protection:** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 235 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 2.1 Vol %

Upper: 18.6 Vol %

· **Vapour pressure at 20 °C:** 5200 hPa

· **Density at 20 °C:** 0.96 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

VOC-(EU) ---

692.1 g/l

· **VOC-EU%** 71.78 %

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 6)

- | | |
|--------------------------------|--|
| · Solids content: | 36.2 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
Vapours have narcotic effect.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB
(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 7)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
15 01 11*	metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1950

· **14.2 UN proper shipping name**

· **ADR** UN1950 AEROSOLS
 · **IMDG** AEROSOLS
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Danger code (Kemler):** Warning: Gases.
 · **EMS Number:** -

· **14.7 Transport in bulk according to Annex II of**

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 8)

· Transport/Additional information:

· ADR

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· IMDG

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .**

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R20/21 Harmful by inhalation and in contact with skin.

R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R36 Irritating to eyes.

R37 Irritating to respiratory system.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmfull: may cause lung damage if swallowed

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Contact:** Anwendungstechnik

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.03.2015

Version number 4

Revision: 24.03.2015

Trade name: MONTANA GOLD Spray Paint all colors, fluo and shock

(Contd. of page 9)

*ICAO: International Civil Aviation Organisation**ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**Expl. 1.1: Explosives, Division 1.1**Flam. Gas 1: Flammable gases, Hazard Category 1**Flam. Aerosol 1: Flammable aerosols, Hazard Category 1**Press. Gas C: Gases under pressure: Compressed gas**Flam. Liq. 2: Flammable liquids, Hazard Category 2**Flam. Liq. 3: Flammable liquids, Hazard Category 3**Acute Tox. 4: Acute toxicity, Hazard Category 4**Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2**Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2**STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3**Asp. Tox. 1: Aspiration hazard, Hazard Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2*

GB