Safety data sheet

in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** Decorative satin paint
- **Trade name: LOOP PRO WRITING TOOLS**
- **Product Code given by the Customer :** LP-106.....LP-367 - LP390.....LP-409 UFI: N8U4-P0UN-T00F-8M6R
- **1.2 Relevant identified uses of the substance or mixture and uses advised against :**
  Aerosol decorative satin paint for "do it yourself" and professional use
- **Sector of Use**
  SU 21 Consumer uses: Families = general population = consumers
  SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category** PROC11 Non industrial spraying
- **Environmental release category**
  ERC8a Wide dispersive indoor use of processing aids in open systems
  ERC8d Wide dispersive outdoor use of processing aids in open systems

- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
  ITAL G.E.T.E. srl Strada per Caselle, 16 - 20081 Morimondo - Milano Tel. 02-9407374 - Fax 02-9407371 – sito Web: www.italgete.it
- **E-mail of the M.S.D.S. responsible person :** info@italgete.it
- **1.4 Emergency telephone number:**
  International Support: https://echa.europa.eu/it/support/helpdesks See Emergency telephone numbers [PDF][EN]
  1. Centro antiveleni, Azienda ospedaliera "Antonio Cardarelli", III Servizio di anestesia e rianimazione, via Antonio Cardarelli 9, Napoli; Tel. 081-7472870/ 0815453333 (24h/24h)
  2. Centro antiveleni, Azienda ospedaliera universitaria Careggi, U.O. Tossicologia medica, via Largo Brambilla 3, Firenze; Tel. 055-7947819 (24h/24h)
  3. Centro antiveleni, Centro nazionale d'informazione tossicologica, IRCCS Fondazione Salvatore Maugeri Clinica del lavoro e della riabilitazione, via Salvatore Maugeri 10, Pavia; Tel. 0382- 24444 (24h/24h)
  4. Centro antiveleni, Azienda ospedaliera NiguardaCa' Grande, piazza Ospedale Maggiore 3, Milano; Tel. 02-66101029 (24h/24h)
  5. Centro antiveleni, Azienda ospedaliera "Papa Giovanni XXIII", tossicologia clinica, Dipartimento di farmacia clinica e farmacologia, piazza OMS 1, Bergamo; Tel. 800883300 (24h/24h)
  6. Centro antiveleni Policlinico "Umberto I", PRGM tossicologia d'urgenza, viale del Policlinico 155,Roma; Tel. Tel. +390649978000 – Notturno e festivo 049978024
  7. Centro antiveleni del Policlinico "Agostino Gemelli", Servizio di tossicologia clinica, largo Agostino Gemelli 8, Roma; Tel. 06-3054343 (24h/24h)
  8. Centro antiveleni, Azienda ospedaliera universitaria riuniti, viale Luigi Pinto 1, Foggia; Tel. 0881-732326
  9. Centro antiveleni, Ospedale pediatrico Bambino Gesù, Dipartimento emergenza e accettazione DEA, piazza Sant'Onofrio 4, Roma; Tel. 06-68593726
  10. Centro antiveleni dell'Azienda ospedaliera universitaria integrata (AOUI) di Verona sede di Borgo Trento, piazzale Aristide Stefani, 1 - 37126 Verona». Tel. 800 011 858 (24h/24h)

*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008 :**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
  The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 1)

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Contain:**
acetone
ethyl acetate
n-butyl acetate
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P211 Do not spray on an open flame or other ignition source.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- **2.3 Other hazards :**
When the aerosol containers are under pressure and heated to temperatures exceeding 50 °C, they will deform themselves and may pose a risk of serious body injuries. The vapours are heavier than air and may form flammable and explosive mixtures with air, even at temperatures below 0 °C. High exposure, in a not well-ventilated areas, will provoke breathing difficulties, narcosis and unconsciousness
The mixture does not contains substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.
The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) ≥ 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table
- **Results of PBT and vPvB assessment**
Accordance to Annex XIII of Regulation (EC) 1907/2006 concerning the Registration, Evaluation, Restriction of chemical substances (see section 3 and 2): does not meet the criteria for classification as PBT and vPvB therefore - not applicable.
Use according to good working pratices, avoiding to disperse the product into the environment.

*
SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:**
Substances hazardous to health or the environment , contained in concentrations equal to or in excess of exemption of EC directives or according to the criteria of REACH , or with a Community limit exposure in the workplace .
Aerosol can, under pressure with a mixture of solvents, resins, pigments, additives and propellant.

- **Components :**

CAS: 68476-40-4 EINECS: 270-681-9 Reg.nr.: 01-2119486557-22-XXXX	hydrocarbons, C3-C4 (propane, butane, isobutane) Flam. Gas 1, H220; Press. Gas, H280	>20-<30%

(Contd. on page 3)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 2)

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX EUH066	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	>20-<30%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX EUH066	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	>10-<20%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX EUH066	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	>10-<20%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	>5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-XXXX	titanium dioxide Carc. 2, H351	≥0-<10%

- **SVHC :** No one SVHC present in the mixture.
- **Additional information**
Hydrocarbons C3-4 Nota K 1,3 Butadiene <0,1%
Titanium Dioxide in powder form containing 1% or more of particles with aerodynamic diameter ≤ 10 µm
Note: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide whichis in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

*
SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information :**
In all cases of doubt, or when symptoms of discomfort persist, seek medical attention. Never give beverages, if the person is unconscious.
- **After inhalation :**
Immediately transport the person to an uncontaminated area. If breathing is weak or stopped apply artificial respiration and seek medical advice immediately. If the person is unconscious, take the body on the late with extension of the head, so that the eventual vomiting goes out.
- **After skin contact :**
Remove contaminated clothes immediately. Wash off immediately with copious quantities of water for at least 10 minutes. Do not use solvents. If irritation persists, consult a doctor
- **After eye contact :**
Wash the eyes with copious amounts of water for 10 minutes, keeping eyelids opened. Eventually remove contact-lens. Protect eyes with sterile gauze. Do not use drops or ointments of any kind before visiting the specialist doctor.
- **After swallowing :**
An accidental ingestion of aerosol product is unlikely to happen. Seek medical advice immediately. Cause vomiting only if the doctor indicates to do so.
- **4.2 Information for doctor**
- **4.2 Most important symptoms and effects, both acute and delayed :**
The lack of oxygen due to exposure to high concentrations may cause asphyxiation.
- **Danger :** Danger of impaired breathing.
- **4.3 Indication of any need to immediately consult a doctor and special treatments**
No further relevant information available.
The mixture contains volatile substances which may cause serious central nervous system depression, with effects such as drowsiness, dizziness, unconsciousness, narcosis.

*
SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents :** Dry powder, carbon dioxide o chemical foams.
- **Unsuitable extinguishing agents:**
Direct jets of water. The fine spray of water is used to cool aerosol containers exposed to fire or heat in order to prevent bursts and explosions.
- **5.2 Special hazards arising from the substance or mixture :**
Can be released in case of fire
Carbon monoxide (CO)

(Contd. on page 4)

Safety data sheet

in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 3)

The heat causes an increase in pressure within aerosol containers, which will deform, burst and can be projected at a considerable distance, with the risk of spread of the fire. Exposure to combustion gases can lead to serious health risks.
Under certain fire conditions, traces of other toxic gases cannot be excluded.
Avoid inhalation of fumes evolved in a fire,use self-contained breathing apparatus and protective clothing,keep at a safe distance.

- **5.3 Advice for firefighters :**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information :**

Before approaching the fire, wear a total fire equipment, completed with a helmet visor with a protection for the neck.

*

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures :**

If the aerosol containers undergo damage that cause leaking, immediately avoid any possible point of inflammation. Do not use tools or machines that can produce sparks. Do not breathe vapours and aerosols. Provide adequate ventilation and immediately isolate the damaged aerosol containers.

- **6.2 Environmental precautions:**

Do not allow to enter the ground/soil.
Collect the liquid phase of the product with absorbent inert material, preventing dumping into sewerage.
Ventilate the contaminated room till the gas are completely dissolved.

- **6.3 Methods and material for containment and cleaning up:** Absorb liquid components with liquid-binding material.
- **6.4 Reference to other sections :**

See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling :** Ensure good ventilation/exhaustion at the workplace.
- **Handling :**

Handle only in well-ventilated areas. Do not use in the presence of flames or other source of possible sparkles. Do not turn on electrical appliances until the vapours are completely dispersed. see also section 8
Avoid contact with eyes.
Follow the normal hygiene rules.

- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect from heat.
Do not spray on flames or red-hot objects.

- **7.2 Conditions for safe storage, including any incompatibilities**

Keep the containers in the original boxes, completely avoiding the possibility of falls or collisions. Do not store in underground rooms, propellant and solvents have a significantly higher density in air. Protect from the sun's rays. Store in cool and dry place, away from sources of heat. Keep away from any source of combustion - Do not smoke. Keep away from oxidizing agents, strongly acidic or alkaline products. Store in places intended for flammable products, with appropriate ventilation and far from electrical appliances thus avoiding the accumulation of electrostatic charges. Observe the provisions prescribed by the Fire Department, according to the quantities stored.

- **Storage :** Store the packaging on solid structures.
- **7.3 Specific end use(s) :**

The product is of general use for paint touch-up or limited areas. The safety advice to prevent P271 is to use only outdoors or in a well ventilated area.

*

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

Values threshold limits exposure of ingredients ACGIH TLV - TWA (Time Weighted Average) for 8 h and TLV STEL (Short-Term Exposure Limit) for 15 min.

(Contd. on page 5)

Safety data sheet

in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 4)

- Components with limit values that require monitoring at the workplace:

68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)	
WEL	Long-term value: 1000 ppm
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm
141-78-6 ethyl acetate	
WEL	Short-term value: 400 ppm Long-term value: 200 ppm
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

- Biological limit valu - DNEL

68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)		
Inhalative	DNEL(GLOB)	16000 mg/m³ (rats) (OECD Guideline 422 EPA OPPTS 870.3650) Huntingdon Life Sciences (HLS) (2010a)
67-64-1 acetone		
Dermal	DNEL (EC)	62 mg/kg (Long term - Dermal - Population)
	DNEL/24h	186 mg/kg (Long term - Dermal - Workers)
Inhalative	DNEL (EC)	1210 mg/m³ (Long term - Inhalation - Workers)
		200 mg/m³ (long-term population)
	DNEL/24h	2400 mg/m³ (Short term - Inhalation - Workers)
141-78-6 ethyl acetate		
Oral	DNEL (EC)	4.5 mg/kg (Long term - Oral - Population)
Dermal	DNEL (EC)	63 mg/kg (Long term - Dermal - Workers)
		37 mg/kg (Long term - Dermal - Population)
Inhalative	DNEL (EC)	734 mg/m³ (Long term - Inhalation - Workers)
		367 mg/m³ (long-term population)
	DNEL/24h	1468 mg/m³ (Short term - Inhalation - Workers)
123-86-4 n-butyl acetate		
Inhalative	DNEL (EC)	480 mg/m³ (Long term - Inhalation - Workers)
		102 mg/m³ (long-term population)
	DNEL/24h	960 mg/m³ (Short term - Inhalation - Workers)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	DNEL (EC)	1.67 mg/kg (Long term - Oral - Population)
Dermal	DNEL (EC)	153 mg/kg (Long term - Dermal - Workers)
		55 mg/kg (Long term - Dermal - Population)
Inhalative	DNEL (EC)	275 mg/m³ (Long term - Inhalation - Workers)
		33 mg/m³ (long-term population)

- Biological limit value - PNEC

67-64-1 acetone	
PNEC STP (EC)	100 mg/L (purification plant)
PNEC (EC)	10.6 mg/L (fresh-water)
	1.06 mg/L (sea-water)
	21 mg/L (émissions occasionnelles)
	30.4 mg/kg (sediment (freshwater))
	3.04 mg/kg (sediment (sea water))
	33.3 mg/kg (soil)

(Contd. on page 6)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 5)

141-78-6 ethyl acetate	
PNEC (EC)	0.2 mg/m³ (orally) 0.26 mg/L (fresh-water) 0.026 mg/L (sea-water) 1.65 mg/L (occasional emission) 650 mg/L (purification plant) 1.25 mg/kg (sediment (freshwater)) 0.125 mg/kg (sediment (sea water)) 0.24 mg/kg (soil)

- **Ingredients with biological limit values:**

67-64-1 acetone	
IBE	50 mg/l Medium: urine Sampling time: ft Parameter: acetone

- **Additional information:**
The particle diameter of the preparation are less than 100 microns; a part of these, indicatively 1% by weight, is less than 10 microns. The mass aerodynamic diameter is 28 microns. These values are, however, vary according to temperature, time of delivery and use patterns.

- **8.2 Exposure controls**
Avoid inhaling gas, vapours and aerosol particles, using a properly ventilated environment, in order to maintain the concentration below the exposure limits.
If the measures of environmental hygiene are not enough to fall below these limits, appropriate respiratory protection must be adopted.
- **General protective and hygienic measures**
The usual precautionary measures should be adhered to general rules for handling chemicals.
Keep away from foodstuffs, beverages and food.
Take off immediately all contaminated clothing
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
Not necessary if room is well-ventilated.
If exposure limits are exceeded, use a full face mask with filter gases, organic vapours and dust, type EN141 & EN143 & EN371
- **Protection of hands:**
In case of prolonged usage, use protective gloves resistant to solvents, such as neoprene or PVA, type EN374
- **Eye protection:**
Wear security glasses whenever there is a possibility of contact with the product.



Gauze goggles EN 166 CE.

Glasses of hermetic protection, resistance to solvents, with side protection, type EN166.
- **Body protection:**
In case of correct use not necessary.
Antistatic shoes and clothing.

*

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance**

Form:	Can under pressure with product and liquefied gas
Colour:	According to product specification
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not applicable to the preparation

(Contd. on page 7)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 6)

- **Change in condition**	
Melting point/Melting range:	Not determined
Boiling point/Boiling range:	< 0 °C
- **Flash point:**	< 0 °C
- **Chemical heat of combustion :**	Superior a 20 kJ/g
- **Inflammability (Directive 2008/47/EEC - 08/04/2008) :**	Extremely flammable
- **Decomposition temperature:**	Not determined.
- **Self-inflammability:**	> 300 °C
- **Danger of explosion:**	Not determined.
- **Critical values for explosion:**	
Lower:	1.9 Vol % (LEL)
Upper:	15.0 Vol % (UEL)
Pressure in the can:	4,0 ± 0,2 bar at 20 °C
Relative density at 20 °C	0.80 +/- 0.01 g/cm³ 0,80 +/- 0,02 a 20 °C
Vapour density	Not determined.
Evaporation rate	Not applicable.
- **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix
- **Partition coefficient (n-octanol/water):**	Not determined.
- **Viscosity:**	
dynamic:	Not determined.
- **9.2 Other information**	Radioactivity: not radioactive.
- **Additional information :**	The product is not explosive;however the heaviest steams could create explosive mixture in the passages and in the pipes of aeration. Then the product could taxe fire in presence of free flames, incandescent masses, electric motors, sparks, accumulation of static electricity or different ignition sources even if located far from the point of use.

*
SECTION 10: Stability and reactivity

- **10.1 Reactivity :** No dangerous reaction if properly used and stored.
- **10.2 Chemical stability :** stable if not heated to temperatures exceeding 50 °C.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions :** No dangerous reaction if properly used and stored.
- **10.4 Conditions to avoid :**
Avoid collisions with pointed objects and avoid falls, which causes perforations or breakage of aerosol containers and consequently spillage of gas and flammable solvents. Avoid exposure to high temperatures or direct sunlight; the heat at temperatures higher than 50 °C, which can cause the outbreak and the projection of the container, even at considerable distances, with the risk of spreading fire.
- **10.5 Incompatible materials:**
Keep away from oxidizing agents , strong acids and strong alkalis, in order to prevent corrosion of the steel containers
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
The product is flammable, burning can give rise to the formation of dangerous decomposition products.
see point 5

*
SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values that are relevant for classification :**		
68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)		
Inhalative	LC50/¼h	14442738 mg/m³ (rats) Clark DG and Tiston (1982) 1443 mg/L (rats) Clark DG and Tiston DJ (1982)

(Contd. on page 8)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 7)

		800000 ppm (rats) Clark DG and Tiston (1982)
	NOAEC/390h	10000 ppm (rats) (OECD Guideline 413 EPA OPPTS 870.3465 (90)) Huntingdon Life Sciences (HLS) (2009b)
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rats)
Dermal	LD50	>20000 mg/kg (rabbits)
Inhalative	LC50/4h	>50 mg/L (rats)
141-78-6 ethyl acetate		
Oral	LD50	>5000 mg/kg bw (rats)
Dermal	LD50	>18000 mg/kg (rabbits)
		>20000 mg/kg-bw (rabbits)
Inhalative	LC50/4h	44 mg/L (rats)
	LCL□/6h	>6000 ppm (rats)
123-86-4 n-butyl acetate		
Oral	LD50	>6400 mg/kg (rats)
Dermal	LD50	>5000 mg/kg (rabbits)
Inhalative	LC50/4h	21 mg/L (rats)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	=>5000 mg/kg (mouse)
Dermal	LD50	=>5000 mg/kg (mouse)
Inhalative	LC50/4h	37 mg/L (rats)
13463-67-7 titanium dioxide		
Oral	LD50	2000 mg/kg (rats)
Dermal	LD50	2000 mg/kg (rabbits)
Inhalative	LC50/4h	5 mg/L (orally)

- **Primary irritant effect:**
- **on the skin:**
Prolonged or repeated contacts with the skin causes the removal of the natural fats and can cause the onset of allergic no contact dermatitis.
- **on the eye:**
Direct contact causes serious irritation. Symptoms may include: tearing, redness, swelling and pain.
Irritant effect.
- **Sensitization:** No sensitizing effect is known.
- **Inhalation :**
Inhalation of high concentrations of organic solvents can cause irritation to the mucous membranes and causes harmful effects to the liver, kidney and nervous system. Symptoms can include headache, dizziness, nausea, muscle weakness, fainting and, in extreme cases, loss of consciousness
Extended exposure to vapours and fogs can lead to irritations of the breathing apparatus.
- **Swallowing :**
The accidental ingestion of aerosol is an unlikely event. Ingestion gives irritation to the throat, the digestive system, nausea, vomiting and diarrhoea. The effects may include those described for inhalation.
No risk under normal conditions of use.
- **Subacute to chronic toxicity:**
Not classified. The product does not meet the classification criteria for the following hazard classes:
Acute and chronic toxicity - Specific target organ toxicity (STOT SE 1-2) single exposure - Specific target organ toxicity (STOT RE 1-2) repeated exposure
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant
- **Sensitisation** Not classified. Based on available data, the product does not meet the classification criteria.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
Not classified. The product does not meet the classification criteria for Carcinogenicity - Mutagenicity - Reproductive Toxicity.

(Contd. on page 9)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 8)

*
SECTION 12: Ecological information

Use according to good working pratices, avoiding to disperse the product into the environment.

- **12.1 Toxicity**

- **Aquatic toxicity:**	
68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)	
IC50	16000 mg/L (rats) (OECD Guideline 422 EPA OPPTS 870.3650) Huntingdon Life Sciences (HLS) (2010a)
LC50/48h	14.22 mg/L (Daphnia) USEPA OPP 2008
LC50/96h	24.11 mg/L (fish) QSAR EPA 2008
67-64-1 acetone	
EC50/96h	302 mg/L (Algae)
LC50/336h	4042 mg/L (fish)
LC50/48h	1680 mg/L (Daphnia)
141-78-6 ethyl acetate	
EC50/48h	260 mg/L (Daphnia)
LC50/48h	5600 mg/L (Desmodesmus subspicatus)
	>5000 mg/L (Algae)
LC50/96h	230 mg/L (Pimephales promelas)
NOEC/168h	2.4 mg/L (Daphnia)
NOEC/72h	>100 mg/L (Scenedesmus substicatus)
123-86-4 n-butyl acetate	
EC50/48h	44 mg/L (Daphnia Magna)
LC50/96h	18 mg/L (Pimephales promelas)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50	408-500 mg/L (Daphnia Magna)
EC50/48h	=>400 mg/L (Daphnia Magna)
LC50/96h	100-180 mg/L (Oncortynchus mykiss)

- **12.2 Persistence and degradability :**
The propellant and the solvents disintegrate quickly in the air with photochemical reactions.
There are no data on the persistence and degradability of the mixture (for data missing on substances not yet comunicated by our Suppliers)
- **12.3 Bioaccumulative potential :**
The propellant and the solvents have low split coefficients n-octanol/water and are not definable as bio accumulative.
Not applicable
- **12.4 Mobility in soil :**
The propellant and the solvents are dispersed quickly in the air, without polluting of the soil.
No data available on mobility in soil (due to missing data on substances not yet supplied by our suppliers)
- **Ecotoxical effects:**
The aquatic toxicologists data of the ingredients listed in section 3, are not very high. They do not require the labelling of symbol of environmental danger and ecological risk phrases on the preparation.
Not applicable.
- **Additional ecological information:**
Considering all colours, the amount of volatile organic compounds VOC are maximum 615 g/l.
Regulation for Reducing the Ozone Formed from Aerosol Coating Product Emissions: LOOP COLOR complying with reactivity limit 0.95 Nonflat Coating
- **General notes:**
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.
- **12.5 Results of PBT and vPvB assessment**
According to Annex XIII of Regulation (EC) 1907/2006 concerning the Registration, Evaluation, Restriction of chemical substances (see section 3 and 2): does not meet the criteria for classification as PBT and vPvB therefore - not applicable.
Use according to good working practices, avoiding to disperse the product into the environment.

(Contd. on page 10)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 9)

- **12.6 Other adverse effects :**
The contained solvents and propellant have a low level of photochemical ozone creation potential,

*
SECTION 13: Disposal considerations

- **13.1 Waste treatment methods :**
Handle eventual residues or working defective pieces as safety rules,already described at the points 7 and 8. The storage of the containers with refuses inside shal be done in a proper and fixed area,well ventilated and away from heating sources and/or from uncompatible materials (Chapter 10), protected by another additional area to contain, that must be incombustible, waterproof, unassailable by the refuses and phisically divided from the raw materials warehouse.
- **Waste disposal key number:**
EWC waste code refering to the empty spray cans : 15 01 10*
Code packaging Ferrous packaging code CER 15.01.04
Code packaging Plastic caps: CER 15.01.02
- **EWC European waste catalogue code reported to the mixture or substance :**
According to the European Waste Catalogue, Waste Codes are not specific to the article, but application specific. Waste codes should be assigned according to the application that was made of this article.
- **Features danger refusal :**
HP3 = Flammable.
HP4 = Irritant
- **Uncleaned packagings:**
- **Recommendation:**
Disposal must be made according to official regulations.
The individual aerosol tin can be removed through the differentiated collection of the town solid refuses, in accordance with the rules of the interested Municipalities.

*
SECTION 14: Transport information

- **14.1 UN-Number**	
- **ADR, IMDG, IATA**	UN1950
- **14.2 UN proper shipping name**	
- **ADR**	1950 AEROSOLS
- **IMDG**	AEROSOLS
- **IATA**	AEROSOLS, flammable
- **14.3 Transport hazard class(es)**	
- **ADR**	



- **Class**	2 5F Gases.
- **Label**	2.1
- **IMDG, IATA**	



- **Class**	2.1
- **Label**	2.1
- **14.4 Packing group**	
- **ADR, IMDG, IATA**	Is not subject to the provisions.
- **14.5 Environmental hazards:**	
- **Marine pollutant:**	No
- **14.6 Special precautions for user**	Warning: Gases.
- **Kemler Number ADR/RID :**	-

(Contd. on page 11)

Safety data sheet
in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 10)

- **EMS Number:**	F-D,S-U
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable.
- **Transport/Additional information:**	The aerosol products, packed limited quantities, under Chapter ADR 3.4 in exemption ADR/RID
- **ADR**	
- **Limited quantities (LQ)**	1L
- **Transport category**	2
- **Tunnel restriction code**	D
- **UN "Model Regulation":**	UN1950, AEROSOLS, 2.1
- **EU Regulation 927/2012 - number of Customs code :**	3208 20 90

*
SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57 - 59 :**
Are not present substances SVHC listed in " CANDIDATE LIST "
- **RoHS regulation :**
There are no substances: Lead, Mercury, Cadmium, hexavalent Chromim. Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDEs) that are listed in the Legislative Decree of March 4, 2014 No. 27 implementing Directive 2011/65/CE (Rohs)
- **Further reference provisions:**
Directive 2008/47/EEC aerosols
Regulation 1907/2006/EEC (REACH)
Regulation 1272/2008/EEC (CLP/GHS)
Regulation 790/2009/EEC
Regulation (UE) N. 453/2010 - 20/05/2010
- **15.2 Chemical safety assessment:**
Exposure scenarios for substances are available which lead to the classification of the mixture.
A Chemical Safety Assessment has not been carried out.

*
SECTION 16: Other information

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
- **Training hints** The training of workers on chemical agents must be conducted in accordance with Directive No. 98/24/EC.
- **Recommended restriction of use**
The information have been filled out to the best of our knowledge on the basis of the National and European regulations. The consumer has the responsibility of using the product, according to the instructions and of taking all the necessary measures for to comply with the laws and local rules regarding security and hygiene of the work and conservation of the environment. The information given must be considered as a description of the security demanded relative to our product. We decline any responsibility for the consequent damages due to improper usage of the product.
- **Abbreviations and acronyms :**
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU) (=COV)

(Contd. on page 12)

Safety data sheet

in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878

Printing date 12.02.2023 Vers. N.: 1 Revision: 12.02.2023

Trade name: LOOP PRO WRITING TOOLS

(Contd. of page 11)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal Concentration in atmosphere for 50% of animal test.
LD50: Lethal dose for 50% test animal
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
STEL: Short Term Exposure Limit
TLV: Theshold Limit Value
TWA: Time Weighted Average
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent very Bioaccumulative
CLP: Classification, Labelling and Packaging
REACH: Registration, Evalutation, Authorization of CHemicals
SVHC : Substance of Very High Concern
PNEC: Predicted No Effect Concentration (Risk Assesment)
ACGIH: American Conference of Governmental Industrial Hygienists.
STEL/C: Short-Term Exposure Limit/Ceiling.
LEL: Lower Explosive Limit
UEL: Upper Explosive Limit
BW: Body weight
NOAEL: No Observed Adverse Effects Level
RoHS: Restriction on the use of Hazardous Substances.
RTECS : Registry of Toxic Effects of Chemical Substances.
NOAEC : No Observed Adverse Effects Concentratin
CER : Catalogo Europeo Rifiuti.
NOAEL : No Observed Adverse Effects Concentration
Carc. 2: Carcinogenicity, Hazard Category 2